

## Material Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

# SPECIAL THINNER FOR K-FLEX ADHESIVES

## 1 IDENTIFICATION OF THE ARTICLE AND OF THE COMPANY/UNDERTAKING

### 1.1 Product Identifier

Product name: K-FLEX SPECIAL THINNER

UFI: JJX0-202Q-E00R-759R

### 1.2 Relevant identified uses of the article/mixture and uses advised against

Intended use: Thinner for adhesives recommended for professional use only. Retail sale and use is prohibited

### 1.3 Details of the supplier of the information sheet

Manufacturer/Supplier:

L'ISOLANTE K-FLEX S.p.A.

via Don Locatelli, 35 20877 Roncello (MB) ITALY

Tel. +39 039 6824.1

e-mail: Kflex-Reach@kflex.com

Further information obtainable from: R&D Dept.

### 1.4 Emergency telephone number

For urgent inquiries refer to

Tel. +39 3333473261 - Gianluca Colombi

## 2 HAZARDS IDENTIFICATION

### 2.1 Classification of the article/mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/830. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Flammable liquid, category 2 H225 Highly flammable liquid and vapour.

Eye irritation, category 2 H319 Causes serious eye irritation.

Specific target organ toxicity - single exposure, category 3 H336 May cause drowsiness or dizziness.

Hazardous to the aquatic environment, chronic toxicity, category 3 H412 Toxic to aquatic life with long lasting effects.

### 2.2 Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:

SPECIAL THINNER FOR K-FLEX ADHESIVES

Page n. 1 of 21

## Material Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

### SPECIAL THINNER FOR K-FLEX ADHESIVES



Signal words: Danger

Hazard statements:

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P280 Wear protective gloves/ protective clothing / eye protection / face protection.

P370+P378 In case of fire: use carbon dioxide, foam, chemical powder. Do not use water.

P261 Avoid breathing dust / fume / gas / mist / vapours / spray.

Contains:

ACETONE

ETHYL ACETATE

Isoalkanes C6 hydrocarbons <5% n-hexane

#### 2.3 Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration  $\geq$  0.1%.

## 3 COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.1 Substances

N.A.

#### 3.2 Article/Mixtures

Contains:

Identification	Classification 1272/2008 (CLP)	x = Conc. %
CAS 141-78-6 EC 205-500-4 INDEX 607-022-00-5 REACH Reg. 01-2119475103-46	ETHYL ACETATE Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066	$60 \leq x < 85$

SPECIAL THINNER FOR K-FLEX ADHESIVES

Page n. 2 of 21

## Material Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

### SPECIAL THINNER FOR K-FLEX ADHESIVES

CAS 67-64-1 EC 200-662-2 INDEX 606-001-00-8 REACH Reg. 01-2119471330-49	ACETONE Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066	20 ≤ x < 30
CAS - EC 931-254-9 INDEX - REACH Reg. 01-2119484651-34	Isoalkanes C6 hydrocarbons <5% n-hexane Flam. Liq. 2 H225, Asp. Tox. 1 H304, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H336, Aquatic Chronic 2 H411	5 ≤ x < 10

The full wording of hazard (H) phrases is given in section 16 of the sheet.

## 4 FIRST AID MEASURES

### 4.1 Description of first aid measures

In case of doubt or in the presence of symptoms contact a doctor and show him this document.

In case of more severe symptoms, ask for immediate medical aid.

**EYES:** Remove, if present, contact lenses if the situation allows you to do so easily. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. Get medical advice/attention.

**SKIN:** Take off contaminated clothing. Wash immediately and thoroughly with running water (and soap if possible). Get medical advice. Avoid further contact with contaminated clothing.

**INGESTION:** Do not induce vomiting unless explicitly authorised by a doctor. Do not give anything by mouth to an unconscious person. Get medical advice/attention.

**INHALATION:** Remove victim to fresh air, away from the accident scene. In the event of respiratory symptoms (coughing, wheezing, breathing difficulty, asthma) keep the victim in a comfortable position for breathing. If necessary administer oxygen. If the subject stops breathing, administer artificial respiration. Get medical advice/attention.

#### Rescuer protection

It is good practice for rescuers lending support to a person who has been exposed to a chemical substance or to a mixture to wear personal protective equipment. The nature of such protection depends on the hazard level of the substance or mixture, on the type of exposure and on the extent of the contamination. In the absence of other more specific indications, use of disposable gloves in the event of possible contact with body fluids is recommended. For the type of PPE suitable for the characteristics of the substance or mixture, see section 8.

### 4.2 Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

**DELAYED EFFECTS:** Based on the information currently available, there are no known cases of delayed effects following exposure to this product.

### 4.3 Indication of any immediate medical attention and special treatment needed

Call a POISON CENTRE / doctor / . . . if you feel unwell.

SPECIAL THINNER FOR K-FLEX ADHESIVES

Page n. 3 of 21

## Material Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

# SPECIAL THINNER FOR K-FLEX ADHESIVES

Means to have available in the workplace for specific and immediate treatment

Running water for skin and eye wash.

## 5 FIRE-FIGHTING MEASURES

### 5.1 Extinguishing media

#### SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

#### UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

### 5.2 Special hazards arising from the substance or mixture

#### HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

### 5.3 Advice for fire-fighters

#### GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

#### SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

## 6 ACCIDENTAL RELEASE MEASURES

### 6.1 Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

### 6.2 Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

### 6.3 Methods and material for containment and cleaning up

SPECIAL THINNER FOR K-FLEX ADHESIVES

Page n. 4 of 21

## Material Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

### SPECIAL THINNER FOR K-FLEX ADHESIVES

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

#### 6.4 Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

---

## 7 HANDLING AND STORAGE

### 7.1 Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

### 7.2 Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

### 7.3 Specific end use(s)

Information not available

---

## 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Control parameters

Regulatory references:

CZE Česká Republika NAŘÍZENÍ VLÁDY ze dne 10. května 2021, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci

DEU Deutschland Forschungsgemeinschaft MAK- und BAT-Werte-Liste 2022 Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe Mitteilung 58

DNK Danmark Bekendtgørelse om grænseværdier for stoffer og materialer - BEK nr 1458 af 13/12/2019

ESP España Límites de exposición profesional para agentes químicos en España 2023

FRA France Valeurs limites d'exposition professionnelle aux agents chimiques en France Décret n° 2021-1849 du 28 décembre 2021

FIN Suomi HTP-VÄRDEN 2020. Koncentrationer som befunnits skadliga. SOCIAL - OCH

SPECIAL THINNER FOR K-FLEX ADHESIVES

Page n. 5 of 21

## Material Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

### SPECIAL THINNER FOR K-FLEX ADHESIVES

HÄLSOVÄRDSMINISTERIETS PUBLIKATIONER 2020:25

GRC Ελλάδα Π.Δ. 26/2020 (ΦΕΚ 50/Α` 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ ``σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξίγονους παράγοντες κατά την εργασία``»

HUN Magyarország Az innovációért és technológiáért felelős miniszter 5/2020. (II. 6.) ITM rendelete a kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről

HRV Hrvatska Pravilnik o izmjenama i dopunama Pravilnika o zaštiti radnika od izloženosti opasnimkemikalijama na radu,graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)

ITA Italia Decreto Legislativo 9 Aprile 2008, n.81

NOR Norge Forskrift om endring i forskrift om tiltaksverdier og grenseverdier for fysiske og kjemiske faktorer i arbeidsmiljøet samt smitterisikogrupper for biologiske faktorer (forskrift om tiltaks- og grenseverdier), 21. august 2018

nr. 1255 PRT Portugal Decreto-Lei n.º 1/2021 de 6 de janeiro, valores-limite de exposição profissional indicativos para os agentes químicos. Decreto-Lei n.º 35/2020 de 13 de julho, proteção dos trabalhadores contra os riscos ligados à exposição durante o trabalho a agentes cancerígenos ou mutagénicos

POL Polska Rozporządzenie ministra rozwoju, pracy i technologii z dnia 18 lutego 2021 r. Zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy ROU România Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru modificarea și completarea hotărârii guvernului nr. 1.093/2006 SWE Sverige Hygieniska gränsvärden, Arbetsmiljöverkets föreskrifter och allmänna råd om hygieniska gränsvärden (AFS 2018:1)

SVK Slovensko NARIADENIE VLÁDY Slovenskej republiky z 12. augusta 2020, ktorým sa mení a doplňa nariadenie vlády Slovenskej republiky č. 356/2006 Z. z. o ochrane zdravia zamestnancov pred rizikami súvisiacimi s expozíciou karcinogénnym a mutagénnym faktorom pri práci v znení neskorších predpisov GBR United Kingdom EH40/2005 Workplace exposure limits (Fourth Edition 2020)

EU OEL EU Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.

TLV-ACGIH ACGIH 2023

ETHYL ACETATE						
Threshold Limit Value						
Type	Country	TWA/8h		STEL/15min		Remarks/Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	CZE	700	191,1	900	245,7	
AGV	DEU	730	200	1460	400	

SPECIAL THINNER FOR K-FLEX ADHESIVES

Page n. 6 of 21

## Material Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

### SPECIAL THINNER FOR K-FLEX ADHESIVES

MAK	DEU	750	200	1500	400	
TLV	DNK	540	150	1468	400	
VLA	ESP	734	200	1468	400	
VLEP	FRA	734	200	1468	400	
HTP	FIN	730	200	1470	400	
TLV	GRC	734	200	1468	400	
AK	HUN	734	200	1468	400	
GVI/KGVI	HRV	734	200	1468	400	
VLEP	ITA	734	200	1468	400	
TLV	NOR	734	200			
VLE	PRT	734	200	1468	400	
NDS/NDSch	POL	734		1468		
TLV	ROU	734	200	1468	400	
NGV/KGV	SWE	550	150	1100	300	
WEL	GBR	734	200	1468	400	
OEL	EU	734	200	1468	400	
TLV-ACGIH		1441	400			

Predicted no-effect concentration - PNEC

Normal value in fresh water 0,24 mg/l

Normal value in marine water 0,024 mg/l

Normal value for fresh water sediment 1,15 mg/kg/d

Normal value for marine water sediment 0,115 mg/kg/d

Normal value for water, intermittent release 1,65 mg/l

Normal value of STP microorganisms 650 mg/l

Normal value for the food chain (secondary poisoning) 0,2 g/kg

Normal value for the terrestrial compartment 0,148 mg/kg/d

Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic

SPECIAL THINNER FOR K-FLEX ADHESIVES

Page n. 7 of 21

## Material Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

### SPECIAL THINNER FOR K-FLEX ADHESIVES

Oral				4,5 mg/kg bw/d				
Inhalation	734 mg/m3	734 mg/m3	367 mg/m3	367 mg/m3	1468 mg/m3	1468 mg/m3	734 mg/m3	734 mg/kg
Skin				37 mg/kg bw/d				63 mg/kg bw/d

ACETONE						
Threshold Limit Value						
Type	Country	TWA/8h		STEL/15min		Remarks/Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	CZE	800	331,2	1500	621	
AGV	DEU	1200	500	2400	1000	
MAK	DEU	1200	500	2400	1000	
TLV	DNK	600	250			E
VLA	ESP	1210	500			
VLEP	FRA	1210	500	2420	1000	
HTP	FIN	1200	500	1500	630	
TLV	GRC	1780		3560		
AK	HUN	1210	500			
GVI/KGVI	HRV	1210	500			
VLEP	ITA	1210	500			
TLV	NOR	295	125			
VLE	PRT	1210	500			
NDS/NDSch	POL	600		1800		
TLV	ROU	1210	500			
NGV/KGV	SWE	600	250	1200 (C)	500 (C)	
NPEL	SVK	1210	500			
WEL	GBR	1210	500	3620	1500	
OEL	EU	1210	500			
TLV-ACGIH			250		500	

Predicted no-effect concentration - PNEC

SPECIAL THINNER FOR K-FLEX ADHESIVES

Page n. 8 of 21

## Material Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

### SPECIAL THINNER FOR K-FLEX ADHESIVES

Normal value in fresh water 10,6 mg/l

Normal value in marine water 1,06 mg/l

Normal value for fresh water sediment 30,4 mg/kg

Normal value for marine water sediment 3,04 mg/kg

Normal value for water, intermittent release 21 mg/l

Normal value of STP microorganisms 100 mg/l

Normal value for the terrestrial compartment 29,5 mg/kg

Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				62 mg/kg				
Inhalation				200 mg/m3		2420 mg/m3		1210 mg/m3
Skin				62 mg/kg				186 mg/kg

Isoalkanes C6 hydrocarbons <5% n-hexane						
Threshold Limit Value						
Type	Country	TWA/8h		STEL/15min		Remarks/Observations
		mg/m3	ppm	mg/m3	ppm	
VLEP	ITA	1200	353			

Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral	VND	1301 mg/kg/d						
Inhalation			VND	1137 mg/m3			VND	5306 mg/m3
Skin			VND	1377 mg/kgbw/d			VND	13964 mg/kg bw/d

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

SPECIAL THINNER FOR K-FLEX ADHESIVES

Page n. 9 of 21

## Material Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

### SPECIAL THINNER FOR K-FLEX ADHESIVES

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ;  
LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

#### 8.2 Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

#### HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

#### SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

#### EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

#### RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a type AX filter, whose limit of use will be defined by the manufacturer (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory

SPECIAL THINNER FOR K-FLEX ADHESIVES

Page n. 10 of 21

## Material Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

# SPECIAL THINNER FOR K-FLEX ADHESIVES

protection device, see standard EN 529.

### ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

## 9 PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties

Properties	Value
Appearance	liquid
Colour	transparent
Odour	characteristic of solvent
Melting point / freezing point	not available
Initial boiling point	55 °C
Flammability	not available
Lower explosive limit	1,2 % (v/v)
Upper explosive limit	13 % (v/v)
Flash point	-18 °C
Auto-ignition temperature	not available
Decomposition temperature	not available
pH	not available
Kinematic viscosity	not available
Solubility	immiscible with water
Partition coefficient: n-octanol/water	not available
Vapour pressure	113,45 mmHg
Density and/or relative density	0,7
Relative vapour density	not available
Particle characteristics	not applicable

### 9.2 Other information

SPECIAL THINNER FOR K-FLEX ADHESIVES

Page n. 11 of 21

## Material Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

### SPECIAL THINNER FOR K-FLEX ADHESIVES

Information with regard to physical hazard classes

Information not available

Other safety characteristics

VOC (Directive 2010/75/EU) 100,00 % - 700,00 g/litre

VOC (volatile carbon) 23,68 % - 165,73 g/litre

## 10 STABILITY AND REACTIVITY

### 10.1 Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

ETHYL ACETATE

Decomposes slowly into acetic acid and ethanol under the effect of light, air and water.

ACETONE

Decomposes under the effect of heat.

### 10.2 Chemical stability

The product is stable in normal conditions of use and storage.

### 10.3 Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

ETHYL ACETATE

Risk of explosion on contact with: alkaline metals,hydrides,oleum.May react violently with: fluorine,strong oxidising agents,chlorosulphuric acid,potassium tert-butoxide.Forms explosive mixtures with: air.

ACETONE

Risk of explosion on contact with: bromine trifluoride,fluorine dioxide,hydrogen peroxide,nitrosyl chloride,2-methyl-1,3 butadiene,nitromethane,nitrosyl perchlorate.May react dangerously with: potassium tert-butoxide,alkaline hydroxides,bromine,bromoform, isoprene, sodium, sulphur dioxide, chromium trioxide, chromyl chloride, nitric acid, chloroform, peroxymonosulphuric acid, phosphoryl oxychloride, chromosulphuric acid,fluorine,strong oxidising agents,strong reducing agents.Develops flammable gas on contact with: nitrosyl perchlorate.

### 10.4 Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

ETHYL ACETATE

Avoid exposure to: light,sources of heat,naked flames.

ACETONE

SPECIAL THINNER FOR K-FLEX ADHESIVES

Page n. 12 of 21

## Material Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

### SPECIAL THINNER FOR K-FLEX ADHESIVES

Avoid exposure to: sources of heat, naked flames.

#### 10.5 Incompatible materials

ETHYL ACETATE

Incompatible with: acids, bases, strong oxidants, aluminium, nitrates, chlorosulphuric acid. Incompatible materials: plastic materials.

ACETONE

Incompatible with: acids, oxidising substances.

#### 10.6 Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

ACETONE

May develop: ketenes, irritant substances.

---

## 11 TOXICOLOGICAL INFORMATION

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation) of the mixture: Not classified (no significant component)

ATE (Oral) of the mixture: Not classified (no significant component)

SPECIAL THINNER FOR K-FLEX ADHESIVES

Page n. 13 of 21

## Material Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

### SPECIAL THINNER FOR K-FLEX ADHESIVES

ATE (Dermal) of the mixture: Not classified (no significant component)

#### ETHYL ACETATE

LD50 (Dermal): > 20000 mg/kg-bw coniglio

LD50 (Oral): 4934 mg/kg dw ratto

#### ACETONE

LD50 (Dermal): > 20 ml/kg coniglio

LD50 (Oral): 5800 mg/kg ratto

LC50 (Inhalation vapours): 21,09 ppm/8h ratto

#### Isoalkanes C6 hydrocarbons <5% n-hexane

LD50 (Dermal): > 5 mg/kg Coniglio

LD50 (Oral): > 5000 mg/kg Ratto

LC50 (Inhalation vapours): > 20 mg/l/1h Ratto

#### SKIN CORROSION / IRRITATION

Repeated exposure may cause skin dryness or cracking.

#### SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

#### RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

#### GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

#### CARCINOGENICITY

Does not meet the classification criteria for this hazard class

#### REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

#### STOT - SINGLE EXPOSURE

May cause drowsiness or dizziness

#### STOT - REPEATED EXPOSURE

SPECIAL THINNER FOR K-FLEX ADHESIVES

Page n. 14 of 21

## Material Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

### SPECIAL THINNER FOR K-FLEX ADHESIVES

Does not meet the classification criteria for this hazard class

#### ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

#### 11.2 Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

## 12 ECOLOGICAL INFORMATION

This product is dangerous for the environment and the aquatic organisms. In the long term, it has negative effects on the aquatic environment.

#### 12.1 Toxicity

##### ACETONE

LC50 - for Fish 8120 mg/l/96h Pimephales promelas

EC50 - for Crustacea 8800 mg/l/48h Daphnia

EC50 - for Algae / Aquatic Plants 530 mg/l/72h Alga

##### ETHYL ACETATE

LC50 - for Fish 230 mg/l/96h Pimephales promelas

EC50 - for Crustacea 165 mg/l/48h Daphnia magna

Chronic NOEC for Crustacea 2,4 mg/l Daphnia pulex

Chronic NOEC for Algae / Aquatic Plants > 100 mg/l Scenedesmus subspicatus

#### 12.2 Persistence and degradability

The paraffinic hydrocarbons fraction may be considered biodegradable in water and in air. They distribute mostly in the air. The small non biodegradable amount which spreads into water tends to accumulate in fish.

##### ACETONE

Rapidly degradable

##### ETHYL ACETATE

Solubility in water > 10000 mg/l

Rapidly degradable

#### 12.3 Bioaccumulative potential

##### ETHYL ACETATE

Partition coefficient: n-octanol/water 0,68

BCF 30

SPECIAL THINNER FOR K-FLEX ADHESIVES

Page n. 15 of 21

## Material Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

### SPECIAL THINNER FOR K-FLEX ADHESIVES

#### 12.4 Mobility in soil

Information not available

#### 12.5 Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

#### 12.6 Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

#### 12.7 Other adverse effects

Information not available

## 13 DISPOSAL CONSIDERATIONS

#### 13.1 Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

## 14 TRANSPORT INFORMATION

#### 14.1 UN number or ID number

ADR / RID, IMDG, IATA: UN 1993


#### 14.2 UN proper shipping name

ADR / RID: FLAMMABLE LIQUID, N.O.S. (ETHYL ACETATE; ACETONE)

IMDG: FLAMMABLE LIQUID, N.O.S. (ETHYL ACETATE; ACETONE)

IATA: FLAMMABLE LIQUID, N.O.S. (ETHYL ACETATE; ACETONE)

#### 14.3 Transport hazard class(es)

ADR / RID:	Class: 3	Label: 3	
------------	----------	----------	---



SPECIAL THINNER FOR K-FLEX ADHESIVES

Page n. 16 of 21

## Material Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

### SPECIAL THINNER FOR K-FLEX ADHESIVES

IMDG:	Class: 3	Label: 3	
IATA:	Class: 3	Label: 3	

#### 14.4 Packing Group

ADR / RID, IMDG, IATA: II

#### 14.5 Environmental hazards

ADR / RID: NO

IMDG: not marine pollutant

IATA: NO

#### 14.6 Special Precautions for User

ADR / RID:	HIN - Kemler: 33	Limited Quantities: 1 L	Tunnel restriction code: (D/E)
	Special Provision: 274, 601, 640C		
IMDG:	EMS: F-E, S-E	Limited Quantities: 1 L	
IATA:	Cargo:	Maximum quantity: 60 L	Packaging instructions: 364
	Pass.:	Maximum quantity: 5 L	Packaging instructions: 353
	Special Instructions:	A3	

#### 14.7 Maritime transport in bulk according to IMO instruments

Information not relevant

## 15 REGULATORY INFORMATION

#### 15.1 Safety, health and environmental regulations/legislation specific for the article/mixture

Seveso Category - Directive 2012/18/EU: P5c-E2

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 3 - 40

Contained substance

SPECIAL THINNER FOR K-FLEX ADHESIVES

Page n. 17 of 21

## Material Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

# SPECIAL THINNER FOR K-FLEX ADHESIVES

Point 75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

Regulated explosives precursor

The acquisition, introduction, possession or use of that regulated explosives precursor by members of the general public is subject to reporting obligations as set out in Article 9.

All suspicious transactions and significant disappearances and thefts must be reported to the relevant national contact point.

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage  $\geq$  than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

### 15.2 Chemical Safety Assessment

A chemical safety assessment has been performed for the following contained substances

ETHYL ACETATE

ACETONE

## 16 OTHER INFORMATION

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 2 Flammable liquid, category 2

Asp. Tox. 1 Aspiration hazard, category 1

Eye Irrit. 2 Eye irritation, category 2

Skin Irrit. 2 Skin irritation, category 2

SPECIAL THINNER FOR K-FLEX ADHESIVES

Page n. 18 of 21

## Material Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

### SPECIAL THINNER FOR K-FLEX ADHESIVES

STOT SE 3 Specific target organ toxicity - single exposure, category 3  
Aquatic Chronic 2 Hazardous to the aquatic environment, chronic toxicity, category 2  
Aquatic Chronic 3 Hazardous to the aquatic environment, chronic toxicity, category 3  
H225 Highly flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H319 Causes serious eye irritation.  
H315 Causes skin irritation.  
H336 May cause drowsiness or dizziness.  
H411 Toxic to aquatic life with long lasting effects.  
H412 Harmful to aquatic life with long lasting effects.  
EUH066 Repeated exposure may cause skin dryness or cracking.

#### LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.

SPECIAL THINNER FOR K-FLEX ADHESIVES

Page n. 19 of 21

## Material Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

### SPECIAL THINNER FOR K-FLEX ADHESIVES

- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

#### GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
23. Delegated Regulation (UE) 2023/707
24. Delegated Regulation (UE) 2023/1434 (XIX Atp. CLP)
24. Delegated Regulation (UE) 2023/1435 (XX Atp. CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition

SPECIAL THINNER FOR K-FLEX ADHESIVES

Page n. 20 of 21

## Material Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

### SPECIAL THINNER FOR K-FLEX ADHESIVES

- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

#### Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

#### CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

SPECIAL THINNER FOR K-FLEX ADHESIVES

Page n. 21 of 21